

# COLMET™

DEFINED BY STEEL™

## PRODUCT SPECIFICATIONS

Product #	Description	Stake/ Pieces	Stake Size	Approx Lbs. Each
1625	16' x 1/4" x 4"	6	12" x 10ga	55.9
1625-5	16' x 1/4" x 5"	6	12" x 10ga	69.5
1625-6	16' x 1/4" x 6"	6	16" x 10ga	83.6
1625-8	16' x 1/4" x 8"	6	16" x 10ga	111.7
1607	16' x 3/16" x 4"	6	12" x 10ga	41.8
1607-5	16' x 3/16" x 5"	6	12" x 10ga	52.2
1607-6	16' x 3/16" x 6"	6	16" x 10ga	62.7
1607-8	16' x 3/16" x 8"	6	16" x 10ga	83.8
1611	16' x 1/8" x 4"	6	12" x 10ga	27.9
1611-5	16' x 1/8" x 5"	6	12" x 10ga	34.7
1611-6	16' x 1/8" x 6"	6	16" x 10ga	41.7
1611-8	16' x 1/8" x 8"	6	16" x 10ga	55.9

## DECIMAL THICKNESS RANGE

Product #	Decimal Range
1625	.25 min.
1607	.1875 min.
1611	.125 min.

**Powder Coat Colors (Semi-Gloss or Textured):  
Brown, Black, Green**  
Unpainted and Galvanized edging also available

## STEEL SPECIFICATION

Hot-rolled low/mild carbon steel meets ASTM-A-1011 CS Type B, produced using a modified 1010 chemistry with .08% max carbon. Material is produced with best practices to meet an expected Rockwell B hardness range of 50 to 75.

## PAINT APPLICATION

Electrostatically applied powder coat specially formulated to withstand extended outdoor exposure in most cases. This coating is ideally suited and commonly used for lawn and garden equipment, fencing, and playground and recreational equipment.

The information contained here is true and accurate to the best of our knowledge. This information is for specified Colmet products and not for use with any other brand of steel edging. Colmet and Defined By Steel are trademarks and cannot be reproduced without written permission.



Colmet LLC | 3333 Miller Park South, Garland TX 75042 | 972-494-3900

Visit our website [colmet.com](http://colmet.com) for more information