

COLMET™

DEFINED BY STEEL™

PRODUCT SPECIFICATIONS

Product #	Description	Pieces	Stakes	Stake Size	Approx Lbs. Each
14TR2	2.5' Diameter 14 ga. Tree-Ring	1	4	12" x 10ga	10.5
14TR3	3' Diameter 14 ga. Tree-Ring	1	4	12" x 10ga	13
14TR4	4' Diameter 14 ga. Tree-Ring	2	7	12" x 10ga	17.5
14TR5	5' Diameter 14 ga. Tree-Ring	2	8	12" x 10ga	21
14TR6	6' Diameter 14 ga. Tree-Ring	2	8	12" x 10ga	26

DECIMAL THICKNESS RANGE

Product #	Decimal Range
14TR2	.0677 to .0817
14TR3	.0677 to .0817
14TR4	.0677 to .0817
14TR5	.0677 to .0817
14TR6	.0677 to .0817

Powder Coat Colors (Semi-Gloss or Textured):
Brown, Black, Green
Unpainted and Galvanized tree rings also available

STEEL SPECIFICATION

Hot-rolled low/mild carbon steel meets ASTM-A-1011 CS Type B, produced using a modified 1010 chemistry with .08% max carbon. Material is produced with best practices to meet an expected Rockwell B hardness range of 50 to 75.

PAINT APPLICATION

Electrostatically applied powder coat specially formulated to withstand extended outdoor exposure in most cases. This coating is ideally suited and commonly used for lawn and garden equipment, fencing, and playground and recreational equipment.

The information contained here is true and accurate to the best of our knowledge. This information is for specified Colmet products and not for use with any other brand of steel edging. Colmet and Defined By Steel are trademarks and cannot be reproduced without written permission.



Colmet LLC | 3333 Miller Park South, Garland TX 75042 | 972-494-3900

Visit our website colmet.com for more information